

**PATENT APPLICATION TRANSMITTAL LETTER**  
(Small Entity)

Docket No.  
DVME-1005US

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Transmitted herewith for filing under 35 U.S.C. 111 and 37 C.F.R. 1.53 is the patent application of:

Wilhelmus Joseph Leonardus SUYKER et al.

For: **Connector, Applicator and Method for Mechanically Connecting Hollow Structures, in Particular Small Blood Vessels**

Enclosed are:


- ☐ Certificate of Mailing with Express Mail Mailing Label No.  
☒ 9 sheets of drawings.  
☐ A certified copy of a application.  
☒ Declaration ☒ Signed. ☐ Unsigned.  
☒ Power of Attorney  
☐ Information Disclosure Statement  
☒ Preliminary Amendment  
☒ Verified Statement(s) to Establish Small Entity Status Under 37 C.F.R. 1.9 and 1.27.  
☒ Other:

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
<b>Total Claims</b>	39	- 20 =	19	x \$9.00	\$171.00
<b>Indep. Claims</b>	8	- 3 =	5	x \$40.00	\$200.00
<b>Multiple Dependent Claims (check if applicable)</b> <input type="checkbox"/>					\$0.00
<b>BASIC FEE</b>					\$355.00
<b>TOTAL FILING FEE</b>					\$726.00

- ☐ A check in the amount of to cover the filing fee is enclosed.  
☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 50-0462 as described below. A duplicate copy of this sheet is enclosed.  
☒ Charge the amount of \$726.00 as filing fee.  
☒ Credit any overpayment.  
☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.  
☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: November 9, 2000

  
Signature

Kevin J. Dunleavy, Esq.  
Registration No. 32,024  
KNOBLE & YOSHIDA, LLC  
Eight Penn Center, Suite 1350  
1628 John F. Kennedy Boulevard  
Philadelphia, PA 19103  
Telephone: 215-599-0600 Fax: 215-599-0601  
Customer no. 21302

cc:

11/05/00 20:42:45;0042113870 -> +31 38 4604089;  
06/11 '00 MAA 18:07 FAX +31 20 5110931 DE VRIES & METMAN  
11/05/2000 23:31 7039319102

Page 005

005/006

PAGE 87/89

Page 1 of 2

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS (37 CFR 1.9(f) AND 1.27 (b)) - INDEPENDENT INVENTOR			Docket No. DVME-1005US
Serial No. NA	Filing Date Filed Herewith	Patent No. NA	Issue Date NA
Applicant/ <u>Wilhelmus Joseph Leonardus SUYKER et al.</u> Patentee:			
Invention. <u>Connector, applicator and method for mechanically connecting hollow structures, in particular small blood vessels</u>			
<p>As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled above and described in:</p> <p><input checked="" type="checkbox"/> the specification to be filed herewith. <input type="checkbox"/> the application identified above. <input type="checkbox"/> the patent identified above.</p> <p>I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).</p> <p>Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below.</p> <p><input checked="" type="checkbox"/> No such person, concern or organization exists. <input type="checkbox"/> Each such person, concern or organization is listed below.</p> <p>*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities (37 CFR 1.27)</p> <p>FULL NAME <u>Wilhelmus Joseph Leonardus SUYKER</u> ADDRESS <u>Zalmkolk 13, NL-8017 PB ZWOLLE The Netherlands</u> <input checked="" type="checkbox"/> Individual <input type="checkbox"/> Small Business Concern <input type="checkbox"/> Nonprofit Organization</p> <p>FULL NAME <u>Paulus Thomas Wilhelmus SUYKER</u> ADDRESS <u>Sijdel 208 F, NL-1016 AA AMSTERDAM The Netherlands</u> <input checked="" type="checkbox"/> Individual <input type="checkbox"/> Small Business Concern <input type="checkbox"/> Nonprofit Organization</p> <p>FULL NAME _____ ADDRESS _____ <input type="checkbox"/> Individual <input type="checkbox"/> Small Business Concern <input type="checkbox"/> Nonprofit Organization</p> <p>FULL NAME _____ ADDRESS _____ <input type="checkbox"/> Individual <input type="checkbox"/> Small Business Concern <input type="checkbox"/> Nonprofit Organization</p>			

Copyright 1994 Legation

P03REV01

Patent and Trademark Office-U.S. DEPARTMENT OF COMMERCE

06/11 '00 MAA 17:23

(TX/RX NR 5421) 007

09/11 '00 DON 03:01

(TX/RX NR 5474) 005

09 nov 00 02:25

Paul Suyker

+31 20-7767096

P. 6

11/06/00 20:42:45; 0842113870

&gt; +31 33 4604089;

Page 006

08/11 '00 MAA 18:06 FAX +31 20 5110931 DE VRIES &amp; METMAN

0006/008

11/05/2000 23:31 7839319182

PAGE 08/08

Page 2 of 2

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INVENTOR Wilhelmus Joseph Leonardus SUYKERSIGNATURE OF INVENTOR DATE: Nov. 6, 2000NAME OF INVENTOR Paulus Thomas Johannes SUYKERSIGNATURE OF INVENTOR DATE: Nov 7, 2000

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

Patent and Trademark Office-U.S. DEPARTMENT OF COMMERCE

06/11 '00 MAA 17:23

[TX/RX NR 3421] 006

09/11 '00 DON 03:01

[TX/RX NR 5474] 008

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:	)	
	)	
Wilhelmus Joseph Leonardus SUYKER et al.	)	
	)	
Serial No.: NA	)	Group Art Unit: NA
	)	
Filed: HEREWITH	)	Examiner: NA
	)	
For: Connector, Applicator and Method for Mechanically Connecting Hollow Structures, in Particular Small Blood Vessels		

**PRELIMINARY AMENDMENT**

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Preliminary to the examination of the above-identified application and calculation of the filing fee, please amend the application as set forth below.

**IN THE CLAIMS**

Claim 27, line 1, delete "or 19"

Claim 28, line 1, delete "or 19"

Please add new claims 38-39 as set forth below:

-- 38. The applicator as claimed in claim 19, wherein the shank-like element is rigid.

39. The application as claimed in claim 19, wherein the shank-like element is flexible.--

**REMARKS**

The foregoing amendment is made to eliminate multiple dependent claims by rewriting claims 27 and 28 as two separate dependent claims.

Favorable consideration and entry of the amendment prior to calculation aof the filing fee and examination of the application are requested.


Respectfully submitted,

Knoble & Yoshida LLC

Dated: November 9, 2000

Knoble & Yoshida LLC  
Eight Penn Center, Suite 1350  
1628 John F. Kennedy Boulevard  
Philadelphia, Pennsylvania 19103  
Telephone: 215-599-0600; Facsimile: 215-599-0601

By:

  
Kevin J. Dunleavy, Esq  
Reg. No. 32,024

Connector, applicator and method for mechanically connecting hollow structures, in particular small blood vessels

The present invention relates to a connector and applicator for mechanically connecting hollow structures, in particular small blood vessels, through so called anastomoses. Such means may for example be used when making a bypass past narrowings or occlusions of arteries caused by arteriosclerosis.

One such connector and applicator are known from WO-A-99/21491 of applicants. This document discloses several embodiments of connectors which are made up of an annular member and circumferentially spaced joining means for holding the vessel walls together in order to make the joint between the vessels. The connectors as disclosed are suitable both for end-to-side and side-to-side anastomoses.

The object of the present invention is to further improve the connector and applicator for making mechanical connections between hollow structures.

To obtain this object, the present invention provides a connector for mechanically connecting hollow structures, in particular small vessels, comprising:

an annular member of deformable material, said member having a center line and being adapted to be permanently deformed by expansion from a first size in a starting position in which it is delivered to a desired anastomoses site, to a second, larger size in a joining position in which it connects the hollow structures, and

circumferentially spaced means for joining abutting walls of the hollow structures together, said means including staple-like elements being adapted to be permanently deformed from a starting position in which the connector is delivered to a desired site, to a joining position in which they engage the hollow structures to connect them, said staple-like elements having at least two free ends and being attached to the annular

member between its free ends and being tapered from the annular member towards their free ends.

This connector according to the invention has various advantages. The expandability of the annular member is  
5 advantageous because, as a result, the size of the connector is small during delivery, whereas the size of the annular member can be adapted to the size of the vessels on the site of the anastomosis. The staple-like elements are very suitable for holding together adjacent vessel walls of the vessels to be  
10 connected. Due to the tapering, the predictability of the plastic deformation, which is required to close the staples, is improved. If the staples should be curved according to a certain curvature, the deformation will start at the tips and progress towards the annular member, which leads to a  
15 predictable deformation. The tapering can take various forms. The staple-like elements may for example be conically or wedge-shaped towards the free ends. Preferably, the radial thickness of the staple-like elements is diminished towards the respective free ends, but also the width may be tapered.

20 In a preferred embodiment, the staple-like elements are substantially straight and parallel to the center line of the annular member. With this arrangement, the connector can have a minimum diameter which facilitates easy handling during an operation. From this straight starting position, the staple-  
25 like elements can be deformed either to a C-shape to form a perfect or overlapping circle, or to a B-shape or an overlapping B-shape.

In order to further increase the predictability of the deformation phase of the staple-like elements, the staple-like  
30 elements may be provided with extreme tips which are preformed into the anticipated curve of the deformation to the joining position.

It is not necessary that the portions of the staple-like elements on either side of the point of attachments to the  
35 annular member are mirror shaped. The length, thickness and slope towards the free ends can be varied to accommodate required bending characteristics or vessel wall thicknesses.

It is preferred to make the connector according to the invention from one piece of material, preferably metal, for example stainless steel 316L or titanium. Connectors which are sufficiently small for use in coronary artery bypass surgery can be manufactured from one piece of metal by using a combination of cutting with a lathe and subsequently using laser techniques or electric erosion techniques. In this way, the connector is made directly in 3D. Alternatively, 2D-techniques like photo-etching and electroplating can be used to make 2D pieces out of thin, flat material. These can be converted into 3D, either by forcing a 2D shape into 3D, or by bending and welding together the beginning and end of the 2D shape.

An easily expandable annular member is obtained if the annular member is made up from a continuous elongated piece of material having a sinusoidal pattern meandering about a circle line through the annular member. In this case, the staple-like elements are preferably formed at an apex of the sinusoidal pattern.

In order to increase the maximum size of the annular member in the joining position, it is preferred to have the main plane of the annular member at an angle to the center line of the annular member.

Due to this feature, the orifice area of the anastomosis can be increased without increasing the size of the connector and applicator, which is limited by the diameter of the hollow structures through which the applicator is inserted. The above feature results in an elliptical anastomosis with an increased orifice area as compared to a circular anastomosis, while the size of the applicator can remain unchanged. In case the main plane of the annular member is at an angle of for example  $45^\circ$ , the area is increased by a factor  $\sqrt{2} = 1.41$ . Practically the staple-like elements of the connector will remain parallel to the center line of the applicator and connector.



The present invention also includes an applicator for delivering and deploying a connector for mechanically connecting hollow structures, comprising:

a shank-like element;

5 a head formed at a distal end of the shank-like element, said head being adjustable in such a manner that the annular member and the staple-like elements of the connector are deformed from the starting position to the joining position when said adjusting takes place,

10 said head including an inner member and an outer member which are longitudinally slidable and include longitudinally opposite anvil formations which are movable to and for upon relative sliding movements of the inner and outer members in order to deform the staple-like elements to their  
15 joining position;

wherein both the inner and outer members are expandable to deform the connector to the joining position.

Due to the expandability of both the inner and outer members, it is possible to minimize the radial dimensions of  
20 the applicator. It is now possible to make the head of the applicator smaller than the radial size of the connector in the joining position, since the outer member of the head of the applicator is enabled to expand together with the connector.

A simple manner to obtain the expandability of the  
25 inner and outer members is to slit or cut them in axial direction. Preferably, the outer member includes at least first slits and second slits, said first slits are arranged at an end of the outer member which forms part of the head and extends between the anvil formations, said second slits being spaced  
30 from said end of the outer member, and alternate with the first slits and are configured in overlapping arrangement.

Due to this configuration of the slits or cuts, the radial as well as the tangential stiffness of the delicate material between the slits is increased. This further assists  
35 in diminishing the dimensions of the head of the applicator.

Another advantageous feature to minimize the radial dimensions of the head is the feature that the anvil

formations, on their sides facing each other, have curved surfaces dictating the deformation of the staple-like elements, said curved surfaces being formed to such an extent that they terminate at an angle to the longitudinal axis of the head which is slightly beyond 90°, for example 91°-120°.

These "low profile" anvil formations make the applicator head as slender as possible, but nonetheless allow for a predictable bending of the staple-like elements of the connector.

10 An alternative applicator according to the invention comprises a shank-like element, and a head formed at a distal end of the shank-like element, said head being adjustable in such a manner that the annular member and the staple-like elements of the connector are deformed from the starting  
15 position to the joining position when said adjusting takes place. The head includes an inner member and an outer member which are longitudinally slidable and include longitudinally opposite anvil formations which are movable to and from upon relative sliding movements of the inner and outer members in  
20 order to deform the staple-like elements to their joining position. The head further includes an expansion member comprising wedges adapted to slide underneath the annular member.

In this embodiment of the applicator according to the  
25 invention, the expansion of the annular member of the connector is effected by the wedges of the expansion member which slide underneath the annular member and thereby urging the annular member outwardly.

One way of enabling the wedges to slide underneath the  
30 annular member is to make the expansion member slidable relative to the inner and outer members, and in this embodiment it is advantageous if the wedges are interleaved with the anvil formations, since the head of the applicator can then be made as small as possible.

35 In this embodiment of the applicator, the simplest design thereof is obtained if the staple-like elements are first deformed to their joining position, whereafter the

annular member is expanded by the wedges of the expansion member. In that case it is not necessary to make the outer member expandable and in a preferred embodiment it is even possible to expand the annular member of the connector and  
5 remove it from the head of the applicator in distal direction over the anvil formations of the inner member in a continued operation.

In another embodiment of the applicator according to the invention, the head includes not only an anastomosis  
10 portion which is adjustable in such a manner that the annular member and the joining elements of the connector are deformed from the starting position to the joining position when said adjusting takes place, but also a punching portion distally of the anastomosis portion and including two relatively movable  
15 parts configured to cause a punching action on a wall of the hollow structure and to catch or trap a punched-out part of said wall.

With such applicator it is possible to both cut a hole in the vessel wall in order to enable the applicator to enter  
20 the vessel, and to perform the anastomosis with the same instrument. This simplifies the procedure and reduces time and cost.

The invention further includes a method of delivering and deploying a connector for mechanically connecting hollow  
25 structures. This method comprises the steps of:

providing a connector for joining adjacent walls of the hollow structures,

providing an applicator for said connector, said applicator including cutting means,

30 making an arteriotomy in the wall of one of the hollow structures,

inserting the cutting means of the applicator partly into said one of the hollow structures through the arteriotomy, so as to cut a hole in the wall,

35 advancing the applicator up to a desired position,

deploying the connector by means of the applicator so as to connect the walls of the hollow structures.

The invention will further be described with reference to the drawings showing embodiments of the invention by way of example.

5           Fig. 1 is a perspective view of an embodiment of the connector according to the invention.

          Fig. 2 is a view of the connector of fig. 1 in radial direction.

10           Fig. 3 is a view of the connector of fig. 1 in axial direction.

          Fig. 4 is a perspective view of an applicator for use with the connector of figs. 1-3, on a smaller scale.

          Fig. 5 is a front view of the applicator of fig. 4.

15           Fig. 6 is a sectional view of the applicator of fig. 4, along the plane VI-VI in fig. 5.

          Fig. 7 is an axial view of the outer member of the applicator of fig. 4, on a larger scale.

20           Fig. 8 is a sectional view of the outer member of fig. 7 along the plane VIII-VIII.

          Fig. 9 is an axial view of the inner member of the applicator of fig. 4, on a larger scale.

          Fig. 10 is a sectional view of the inner member of fig. 9, taken along the line X-X.

25           Fig. 11 is a very schematic perspective view of members forming the head of an alternative embodiment of the applicator according to the invention.

          Fig. 12 is a sectional view along the line XII-XII in fig. 11.

30           Figs. 13A-13C are longitudinal sectional views of the applicator head of fig. 11, in three different positions during deployment of the connector.

          Fig. 14 is a very schematic side view of an alternative embodiment of the connector according to the invention.

35           Fig. 15 is a very schematic side view of the head of an applicator for delivering and deploying the connector of Fig. 14.

Fig. 16 is a very schematic, partly cut-away side view of the head of a further embodiment of an applicator according to the invention.

Figs. 1-3 show an embodiment of a connector for mechanically connecting hollow structures, in particular small blood vessels, such as coronary arteries. The connector is specially designed for making a side-to-side anastomosis but may also be used or adapted to make other connections, for example an end-to-side anastomoses or other joints.

The connector as shown comprises an annular one and a plurality of joining means in the form of staple-like elements to spaced around the circumference of the annular member 1. The annular member and staple-like elements are preferably formed from one piece of material, preferably metal such as stainless steel 316L or titanium.

The annular member as shown in figs. 1-3 comprises a continuous elongated element having a sinusoidal pattern meandering about a circle line through the annular member. The alternating waves 3 and 4 of the pattern have a different wave length in order to accommodate the staple-like elements 2 which are formed at each wave 4, at the apex thereof. The meandering pattern of the annular member 1 creates the expandability of the annular member by widening the meanders or waves of the pattern thereby increasing the diameter of the annular member 1. The deformation of the annular member 1 is plastically, so that the annular member 1 will retain its shape after expansion.

The configuration of the annular member 1 may vary within a broad range, including the length of the annular member 1. The term annular also covers tubular members.

The staple-like elements 2 comprise two staple portions 5, 6 which extend from the point of attachment to the annular member 1 in opposite directions. In the embodiment shown, both staple portions 5, 6 are aligned and are substantially each other's mirror image, but it should be kept in mind that that need not be the case. Instead thereof, the length, thickness and slope towards the free ends of the staple

portions 5,6 can be varied to accommodate required bending characteristics or vessel wall thicknesses.

As is shown in figs. 1-3, in which the connector is shown in its starting position in which it is delivered to the anastomosis site, the staple-like elements are substantially straight and extend parallel to the center axis of the annular member. The staple portions 5, 6 are slightly tapered towards their free ends, both in radial thickness and in circumferential width. The tapering is on the outer side of the staple portions 5, 6, whereas the radial inner side of the staple portions 5, 6 extends parallel to the center axis. The circumferential sides of the staple portions 5, 6 are inclined relative to a radial plane through the center of the staple portions 5, 6 such that the width of a staple-like element 2 is smaller on the radial inner side than on the radial outer side. If desired, the extreme tips of the staple portions 5, 6 may be preformed into the anticipated curve, to increase the predictability of the deformation of the staple portions 5, 6. The waves 3 may also be slightly tapered, i.e. having a diminishing thickness in axial direction in the same manner as the adjacent staple portions 5.

Figs. 4-10 show an embodiment of the applicator according to the invention. The applicator includes a main body 7, a grip 8 extending downwardly therefrom on the rear end, a control lever 9 pivotally connected to the front end of the main body 7 and extending downwardly, and a stroke limiter 10 pivotally attached to the lower end of the control lever 9 and slidably connected to the lower end of the grip 8. A pin slot connection 11 between the stroke limiter 10 and the grip 8 determines the maximum stroke of the control lever 10. The control arm may be locked in position by locking the stroke limiter 10 to the grip 8. The control lever 9 is pivotally connected to an intermediate pivot 12 in order to provide a long lever arm 13 and a short lever arm 14. The end of the short lever arm 14 is pivotally connected to a sliding block 15, the sliding motion being guided and limited through a bolt 16.

Attached to the sliding block 15 is an outer tube member 17 and attached to the main body 7 is an inner tube member 18. The inner and outer members 17, 18 together form a shank-like element and on the free end thereof a head 20 adapted to accommodate a connector in order to deliver it to the anastomosis site and to deploy it into a joining position. Figs. 7 and 8/8a show the outer tube member 17 and figs. 9 and 10/10a show the inner tube member 18 in more detail. Inside of the inner tube member is an expansion core connected to an expansion control means 22.

The outer member 17 is provided on its distal end with proximal anvil formations or anvils 23 having a curved surface 24 facing, in an assembled condition, corresponding curved surfaces 25 of distal anvil formations or anvils 26 provided on the distal end of the inner member 18. The number of distal and proximal anvils 23, 26 is equal to the number of staple-like elements 2 of each connector, in this case 8. The anvils 23, 26 are distributed around the circumference of the inner and outer members 17, 18 in the same manner as the staple-like elements on the connector, in this case equally spaced around the circumference. The inner member 18 is provided with a seat 27, proximal of the anvils 26, to accommodate the connector during delivery and in this starting position of the applicator and connector, the inner and outer members 17, 18 have such relative position that the connector is positioned between adjacent anvils 23 and 26 of the inner and outer members 17, 18, with each staple-like element 2 being aligned with respective anvils 23, 26.

In order to be able to expand the connector which is seated on the seat 27 of the inner member 18, this inner member is slitted with cuts or slits 28 extending from the distal end of the inner member 18 a distance in proximal direction. The length of the slits is such that the tongues left between the slits 28 may undergo a sufficient radial deflection to expand the connector to a sufficient extent. The length of the slits may for example be 5-10 times the diameter of the inner member 18. The lumen 29 through the inner tube member 18 has a flaired

end part 30, in which the diameter of the lumen is increased in distal direction, for example at an angle of approximately 30°. This end part 30 is adapted to accommodate the tapered end part of the expansion core 21, so that when the expansion core 21 is retracted in proximal direction by the expansion control means 22, the tapered end part urges the tongues between the slits 28 of the inner tube member 18 outwardly so that the connector present on the seat 27 is expanded.

As is shown in figures 7 and 8, also the outer tube member 17 is slitted. The outer tube member 18 comprises first slits 31 extending from the distal end of the outer tube member 17 a distance in proximal direction, and partly overlapping second slits 32 which alternate with the first slits 31 and extend from a position intermediate the ends of the first slits 31 to a position proximal of the first slits 31. The total length of the first and second slits may for example be 5-10 times the diameter of the outer member 18. Due to this slit arrangement, the radial and tangential strength of the outer member 17 is increased.

The operation of the applicator and connector as shown and described before is as follows.

The shank-like element 19 with a connector positioned on the seat 27 of the head 20 is inserted into one of the vessels to be joined and is delivered to the site where the anastomosis should be accomplished. The control lever 9 is in the position as shown in fig. 4. If the head 20 and therefore the connector is positioned correctly with respect to vessel walls which are positioned around the connector, the expansion control means 22 is actuated to retract the expansion core 21 so as to expand the inner member 18 and therefore the annular member 1 of the connector. Since the outer tube member 17 is also slitted, it is possible for the outer member 17 to follow the expansion of the inner member. As a result the anvil formations 23 and 26 remain substantially in their relative opposite positions, so that, after expansion of the annular member 1 of the connector, it is possible to activate the



anvils 23, 26 in order to deform the staple-like elements 2 of the connector.

The activation of the anvils 23, 26 is effected by sliding the outer tube member 17 in distal direction along the inner member 18 so as to bring the opposite anvils 23, 26 closer to each other thereby engaging the initially straight staple portions 5, 6 of the staple-like elements 2 and upon a further approaching movement of anvils 23, 26 the staple portions 5, 6 follow the curvature of the curved surfaces 24, 25 of the anvils 23, 26. The curved surfaces 24, 25 are shaped as circular segments, which extend through approximately 91-120°, and preferably 115°, which is sufficient to allow a full deformation of each staple portion 5, 6. Depending on the lateral and radial curvature of the surfaces 24, 25, staple portions 5, 6 are deformed either to a C-shape to form a perfect or overlapping circle, or to a B-shape or an overlapping B-shape. After both the annular member 1 and the staple-like elements 2 are deformed into their joining position, the staple portions 5, 6 clamp the vessel walls of adjacent vessels between each other thereby effecting an anastomosis. The expansion core 21 can then be moved back to the starting position so that both the inner and outer members are collapsed into their unexpanded condition in which the outer dimensions of the distal anvil formations 26 is smaller than the inner dimension of the annular member 1 of the connector in expanded condition, so that the applicator can be withdrawn from within the annular member 1 of the connector so as to be removed from the vessel and the body of the patient.

Figures 11-13 show an alternative embodiment of an applicator according to the invention, which may be used to deliver and deploy the connector of figs. 1-3. Figures 11-13 show a head 120 of the shank-like element of the applicator, said head being formed by an outer member 117 and an inner member 118. The inner member has a seat 127 and distal anvils 126. The outer member 17 has proximal anvils 123 between each two adjacent anvils 123. There is created a gap 133 of sufficient axial length to accommodate wedges 134 and provided

on the distal end of an expansion member 135. The expansion member 135 fits slidingly around the outer member 117 such that the wedges are positioned in their respective gap 133 between adjacent anvils 23 or distally thereof. The wedges 134 extend  
 5 inwardly from the tube-like expansion member 135 up to the outer diameter of the inner member 118, so that the extreme tips of the wedges 134 engage the outer surface of the inner member 118. The extreme tips of the wedges 134 are sharp so as to facilitate them to slide underneath the annular member 1 so  
 10 as to engage the annular member 1 and upon a distal sliding movement of the expansion member 135 relative to the inner and outer members 117, 118, the annular member 1 of the connector 1 is expanded by the wedges 134.

In this embodiment, the deformation of the staple-like  
 15 elements 2 take place before the expansion of the annular member 1, so that the inner and outer members 117, 118 are actuated first in order to close the staple-like elements 2 (Fig. 13a-13b), whereafter the expansion member 135 is moved in distal direction so as to expand the annular member 1 and urge  
 20 it over the anvil formations 126 so as to remove the connector from the head 120 of the applicator (Fig. 13c).

Fig. 14 shows an alternative embodiment of a connector for connecting the walls of hollow structures, in particular small vessels through an anastomosis. The connector includes an  
 25 annular member 201 having staple-like elements 202. The annular member 201 and staple-like elements 202 are very similar to those of the embodiment of fig. 1, with the exception of one aspect. The connector has a center line C which is in the center of the lumen through the connector. The connector also  
 30 includes a main plane M which extends through the middle of the annular member. In this embodiment, the center line C is at an angle to the main plane M, which is different from 90°. In the present case, the angle within the plane of the drawing is circa 45°. The staple-like elements 202 extend parallel to the  
 35 center line C.

The reason for using this embodiment is as follows. The maximum size (orifice area) of the anastomosis is limited

by the size of the connector and applicator, which in turn is limited by the diameter of the vessel through which the applicator and connector are inserted. In order to increase the orifice area of the anastomosis, the plane of stapling can be tilted, for example 45°. After expansion to the joining position, this results in an elliptical anastomosis with an increased orifice area (in this case  $\sqrt{2} = 1.41$ ) as compared to a circular anastomosis, whereas the size of the applicator remains unchanged. Thus, it is possible to create bigger anastomoses through a blood vessel having a particular size.

In practice, the staple-like elements 202 of the connector will remain parallel to the central axis of the applicator, while the meandering ring will extend at an angle of 45° to a plane which is perpendicular to the center line C. The meandering waves 203, 204 are, however, within the circular cylinder around the center line C.

Fig. 15 shows a head 220 of an applicator to deliver and deploy the connector according to Fig. 14. As is shown, the position of the proximal and distal anvil formations 223, 226 are adapted to the relative position of the staple-like elements 202.

Fig. 16 shows a further embodiment of an applicator for making anastomoses. In anastomosis procedures, it is often desirable to punch out a hole in the vessel wall at the site of the anticipated anastomosis. This is especially the case when doing the proximal anastomosis in CABG (coronary artery bypass grafting) operations, where for example a piece of saphenous vein graft has to be connected to the ascending aorta, which is a big (30 mm) artery and has a significant wall thickness (2-3 mm). However, on a much more delicate scale, punching out a small hole for the distal anastomosis on the coronary artery itself could also prove to be advantageous.

The embodiment of the applicator according to fig. 16 has means to punch out a hole in the vessel wall incorporated in the head thereof. Fig. 16 shows that the head of this embodiment includes an anastomosis portion 336 and a punching portion 337. This punching portion 337 is positioned distally

of the anastomoses portion 336. The punching portion 337 includes two relatively movable parts, a distal part 338 and a proximal part 339. The distal part 338 is mounted on a core 340 running through the head and shank and is adapted to be operated in order to move axially with respect to the proximal part 339. On their sides facing each other, both parts 338 and 339 are provided with cutting means, including a circular knife 341 on the proximal portion 339 and a counter edge 342. The circular knife 341 is sized to accurately slide over the distal part 338 while performing a cutting action in co-operation with the edge 342. The distal front of the distal part 338 is rounded for easy insertion into an arteriotomy. Alternatively, this rounded front can be replaced by a knife or a conical shape, ending in a sharp point. This configuration permits creating an arteriotomy, punching out a hole and securing the anastomosis with one instrument and requiring only one instrument insertion. To punch the hole this rounded front of the distal part 338 is inserted into the arteriotomy, subsequently this distal part 338 is pulled against the circular knife 341 of the proximal part 339. A circular piece of vessel wall is then cut out and remains trapped between and inside the distal and proximal parts 338, 339 which together enclose this vessel wall piece. This entrapment is important since loose tissue fragments can embolize.

Subsequently, the applicator is pushed further inwardly so that the anastomosis portion 336 is brought in line with the vessel walls to be joined. The expansion mechanism of the anastomosis portion 336 is activated by further retracting the core 340 and distal part 338 in order to push the expansion core 321 (formed on the proximal part 339) in proximal direction with respect to the anastomosis portion 336 so as to expand the seat 327 where the connector is positioned. The further operation of the applicator is similar to that of the embodiment of Figs. 4-10.

This embodiment has the unique feature of being capable to punch a hole and secure the anastomosis during one instrument insertion. Because it is not necessary to remove the

applicator between these two manipulations, there is very limited blood loss and maximum control. This makes the applicator very suitable for making proximal anastomoses on the aorta in port access CABG.

- 5           Alternatively, the punch mechanism could be replaced by a single, linear knife, which makes a linear arteriotomy. The applicator is then advanced through this arteriotomy and deforms it to a more circular shape.

- 10           From the foregoing it is clear that the present invention provides a connector, applicator and method for mechanically connecting small blood vessels and the like in a simple, reliable and efficient manner.

- 15           The punch mechanism could also be replaced by a simple, circular knife. A pointed wire with a simple retaining mechanism like a hook, extending distally to the circular knife would puncture the vessel wall before cutting and would hold the piece of vessel wall after cutting to prevent it from embolizing in the patient.

- 20           The invention is not restricted to the embodiments shown in the drawing and described herein before and can be varied within the scope of the accompanying claims.

## WE CLAIM:

1. A connector for mechanically connecting hollow structures, in particular small vessels, comprising:

an annular member of deformable material, said member having a center line and a main plane, and being adapted to be permanently deformed by expansion from a first size in a starting position in which it is delivered to a desired anastomosis site, to a second, larger size in a joining position in which it connects the hollow structures, circumferentially spaced means for joining abutting walls of the hollow structures together, said means including staple-like elements being adapted to be permanently deformed from a starting position in which the connector is delivered to a desired site, to a joining position in which they engage the hollow structures to connect them, said staple-like elements having at least two free ends and being attached to the annular member between its free ends and being tapered from the annular member towards their free ends.

2. The connector as claimed in claim 1, wherein at least the radial thickness of the staple-like elements is diminished towards the respective free ends.

3. The connector as claimed in claim 1, wherein a center line of each of the staple-like elements is disposed substantially within a radial plane of the annular member.

4. The connector as claimed in claim 2, wherein the staple-like elements are substantially straight in their starting position.

5. The connector as claimed in claim 3, wherein the staple-like elements have extreme tips which are preformed into the anticipated curve of the deformation to the joining position.

6. The connector as claimed in claim 1, wherein the connector is made from one piece of material.

7. The connector as claimed in claim 1, wherein parts of the staple-like elements on opposite sides of their

point of attachment to the annular member are configured differently.

8. The connector as claimed in claim 1, wherein the annular member is made up from a continuous elongated piece of material having a sinusoidal pattern meandering about a circumferential line through the main plane of the annular member.

9. The connector as claimed in claim 8, wherein the staple-like elements are formed at an apex of the sinusoidal pattern.

10. The connector as claimed in claim 1, wherein the main plane is at an angle to the center line of the annular member different from  $90^{\circ}$ .

11. An applicator for delivering and deploying a connector for mechanically connecting hollow structures, said connector including an expandable annular member and a plurality of deformable staple-like elements spaced around the circumference of the annular member, comprising:

a shank-like element;  
a head formed at a distal end of the shank-like element, said head being adjustable in such a manner that the annular member and the staple-like elements of the connector are deformed from the starting position to the joining position when said adjusting takes place,

said head including an inner member and an outer member which are longitudinally slidable and include longitudinally opposite anvil formations which are movable to and from upon relative sliding movements of the inner and outer members in order to deform the staple-like elements to their joining position;

wherein both the inner and outer members are expandable to deform the connector to the joining position.

12. The applicator as claimed in claim 11, wherein both the inner member and the outer member is slitted in axial direction to allow expansion.

13. The applicator as claimed in claim 12, wherein the outer member includes at least first slits and second

slits, said first slits are arranged at an end of the outer member which forms part of the head and extends between the anvil formations, said second slits being spaced from said end of the outer member, and alternate with the first slits and are  
5 configured in overlapping arrangement.

14. The applicator as claimed in claim 12, adapted to expand the annular member and deform the staple-like elements in two steps, wherein the inner member is hollow and the applicator further comprises a tapered core member which is  
10 slidable through the inner member and is operatively connected to a control means to slide the core member into and out of the head to expand the inner and outer members.

15. The applicator as claimed in claim 13, wherein the core member and control means are used to control the  
15 relative movements of the inner and outer members as well.

16. The applicator as claimed in claim 11, wherein the anvil formations, on their sides facing each other, have curved surfaces dictating the deformation of the staple-like elements, said curved surfaces are formed to such an extent  
20 that they terminate at an angle to the longitudinal axis of the head which is slightly beyond 90°, for example 91°-120°.

17. The applicator as claimed in claim 16, wherein the curved surface is shaped as a circular segment which is slightly larger than 90°.

25 18. The applicator as claimed in claim 11, including a grip for handling the applicator, said grip being attached to the proximal end of the shank-like element and including the control means for actuating at least the inner and outer members.

30 19. An applicator for delivering and deploying a connector for mechanically connecting hollow structures, said connector including an expandable annular member and a plurality of deformable staple-like elements spaced around the circumference of the annular member, comprising:

35 a shank-like element;  
a head formed at a distal end of the shank-like element, said head being adjustable in such a manner that the



annular member and the staple-like elements of the connector are deformed from the starting position to the joining position when said adjusting takes place,

5       said head including an inner member and an outer member which are longitudinally slidable and include longitudinally opposite anvil formations which are movable to and for upon relative sliding movements of the inner and outer members in order to deform the staple-like elements to their joining position;

10       said head further including an expansion member comprising wedges adapted to slide underneath the annular member.

20.   The applicator as claimed in claim 19, wherein the expansion member is slidable relative to the inner and 15 outer members.

21.   The applicator as claimed in claim 20, wherein the wedges are interleaved with the anvil formations.

22.   The applicator as claimed in claim 20, wherein the inner member is adapted to support the annular member in 20 its starting position.

23.   The applicator as claimed in claim 20, further including control means adapted to first actuate the inner and outer member to deform the staple-like elements to the joining position, and then to actuate the expansion member in order to 25 expand the annular member to the joining position.

24.   The applicator as claimed in claim 20, wherein the anvil formations on the inner member have an outer dimension which is smaller than the maximum outer dimension of the expansion member, such that the connector can be removed 30 from the applicator in the distal direction over the anvil formations on the inner member.

25.   The applicator as claimed in claim 22, wherein the expansion member includes a tube-like member arranged around the outer member, said tube-like member having the 35 wedges attached to its distal end, said wedges extending inwardly to the outer surface of the inner member.

26.   The applicator as claimed in claim 25, wherein

the outer member has indentations between the proximal anvil formations to accommodate the wedges in a starting position thereof.

27. The applicator as claimed in claim 11 or 19,  
5 wherein the shank-like element is rigid.

28. The applicator as claimed in claim 11 or 19,  
wherein the shank-like element is flexible.

29. An applicator for delivering and deploying a  
connector for mechanically connecting hollow structures, said  
10 connector including an expandable annular member and a  
plurality of deformable joining elements spaced around the  
circumference of the annular member, comprising:

a shank-like element;

a head formed at a distal end of the shank-like  
15 element, said head including an anastomosis portion which is  
adjustable in such a manner that the annular member and the  
joining elements of the connector are deformed from the  
starting position to the joining position when said adjusting  
takes place, said head further including a punching portion  
20 distally of the anastomosis portion and including two  
relatively movable parts configured to cause a punching action  
on a wall of the hollow structure and to catch a punched-out  
part of said wall.

30. The applicator as claimed in claim 29, wherein  
25 the two parts of the punching portion are axially movable and  
include a distal part shaped to be inserted into an arteriotomy  
of the hollow structure, and a proximal part, said distal and  
proximal parts including cooperating knife members facing each  
other and adapted to catch the punched-out part between said  
30 distal and proximal parts.

31. The applicator as claimed in claim 30, wherein  
the anastomosis portion and the puncture portion are supported  
by a core member extending through the head of the applicator.

32. The applicator as claimed in claim 29, wherein a  
35 distal front of the punching portion of the head comprises  
cutting means to cut an arteriotomy in one of the hollow  
structures.

33. A method of delivering and deploying a connector for mechanically connecting hollow structures, said method comprising the steps of:

- providing a connector for joining adjacent walls of
- 5 the hollow structures,
- providing an applicator for said connector, said applicator including cutting means,
- making an arteriotomy in the wall of one of the hollow structures,
- 10 inserting the cutting means of the applicator partly into said one of the hollow structures through the arteriotomy, so as to cut a hole in the wall,
- advancing the applicator up to a desired position,
- deploying the connector by means of the applicator so
- 15 as to connect the walls of the hollow structures.

34. The method as claimed in claim 32, wherein the arteriotomy is made by a second cutting means provided on a distal front of the applicator.

- 35. An applicator for delivering and deploying a
- 20 connector for mechanically connecting hollow structures, said connector including an expandable annular member and a plurality of deformable joining elements spaced around the circumference of the annular member, comprising:

- a shank-like element; and
- 25 a head formed at a distal end of the shank-like element, said head including an anastomosis portion which is adjustable in such a manner that the annular member and the joining elements of the connector are deformed from the starting position to the joining position when said adjusting
- 30 takes place, said head having a distal front which comprises cutting means to cut an arteriotomy in one of the hollow structures.

36. A connector for mechanically connecting hollow structures, in particular small vessels, comprising:

- 35 an annular member of deformable material, said member having a center line and a main plane, and being adapted to be permanently deformed by expansion from a first size in a

starting position in which it is delivered to a desired anastomosis site, to a second, larger size in a joining position in which it connects the hollow structures,

circumferentially spaced means for joining abutting  
 5 walls of the hollow structures together, said means including staple-like elements being adapted to be permanently deformed from a starting position in which the connector is delivered to a desired site, to a joining position in which they engage the hollow structures to connect them,

10 wherein the main plane through the annular member and the center line thereof are at an angle to each other.

37. A connector for mechanically connecting hollow structures, in particular small vessels, comprising:

an annular or tubular member of deformable material;  
 15 said member being adapted to be permanently deformed from a first size in a starting position in which it is delivered to a desired site, to a second, larger size in a joining position in which it connects the hollow structures,

circumferentially spaced means for joining abutting  
 20 walls of the hollow structures together, said means including staple-like elements being adapted to be permanently deformed from a starting position in which the connector is delivered to a desired site, to a joining position in which they engage the hollow structures to connect them, said staple-like elements  
 25 being attached to the annular member near their center and extend in a direction parallel to the center line of the annular member.

**ABSTRACT**

The invention relates to a connector, applicator and method for mechanically connecting hollow structures, in particular small blood vessels, in order to make an anastomosis. The connector incorporates various features to create a reliable engagement with the vessel walls to make a good connection thereof.

The connector comprises knife members to make an arteriotomy in and punch a hole in one of the vessel walls, comprises an expansion portion to cause a large expansion with a minimum profile, and comprises anvil members to reliably bring the staple-like elements to the joining position.




Fig. 1




FIG. 2





FIG. 3







000000000000000000




Fig. 8




Fig. 7





FIG. 10








FIG. 11

7/9






Fig. 15




Fig. 14

2025 RELEASE UNDER E.O. 14176




Fig. 16

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: )  
 )  
Wilhelmus Joseph Leonardus SUYKER et al. )  
 )  
Serial No.: NA ) Group Art Unit: NA  
 )  
Filed: HEREWITH ) Examiner: NA  
 )  
For: Connector, Applicator and Method for Mechanically Connecting Hollow  
Structures, in Particular Small Blood Vessels

CUSTOMER NUMBER FOR CORRESPONDENCE ADDRESS

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Please record the following attorneys'-of-record USPTO Customer Number in the  
above-referenced application.


**21302**

Respectfully submitted,

Knoble & Yoshida LLC

Dated: November 9, 2000

Knoble & Yoshida LLC  
Eight Penn Center, Suite 1350  
1628 John F. Kennedy Boulevard  
Philadelphia, Pennsylvania 19103  
Telephone: 215-599-0600; Facsimile: 215-599-0601

By:   
Kevin J. Dunleavy, Esq  
Reg. No. 32,024

11/06/00 20:42:47;0842113870

-&gt; +31 38 4604089;

Page 002

06/11 '00 MAA 18:04 FAX +31 20 5110931 DE VRIES &amp; METMAN

002/006

11/05/2000 23:31 7839319182

PAGE 04/08

Express Mail Label No.

Page 1 of 3

Docket No.  
DVME-1005US

## Declaration and Power of Attorney For Patent Application

### English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name, - - - - -

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**Connector, applicator and method for mechanically connecting hollow structures, in particular small blood vessels**

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as United States Application No. or PCT International

Application Number \_\_\_\_\_

and was amended on \_\_\_\_\_

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>

Form PTO-38-01 (2-83) (Modified)

PO2/REV2

Patent and Trademark Office-U.S. DEPARTMENT OF COMMERCE

09/11 '00 MAA 17:23

[TX/RX NR 54211] 004

09/11 '00 DON 03:01

[TX/RX NR 5474] 002



11/06/00 20:42:45;0842113870 -> +31 38 4604089;  
06/11 '00 MAA 18:05 FAX +31 20 5110931 DE VRIES & METMAN  
11/05/2000 23:31 7039319182

Page 003

003/006

PAGE 05/00

Page 2 of 3

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)  
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)  
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)  
(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

11/06/00 20:42:45;0842113070

-> +31 38 4604089;

Page 004

00/11 '00 MAA 18:00 FAX +31 20 5110931 DE VRIES & METMAN

004/006

11/05/2000 23:31 7029319107

PAGE 06/88

Page 3 of 3

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Kevin J. Dunleavy, Esq., Reg. No. 32,024

John Knoble, Esq., Reg. No. 32,387

Kenneth Yoshida, Esq., Reg. No. 37,009

Knoble & Yoshida LLC

Eight Penn Center, Suite 1350

1628 John F. Kennedy Boulevard

Philadelphia, Pennsylvania 19103

Telephone: 215-599-0600


Facsimile: 215-599-0601


Send Correspondence to:

Kevin J. Dunleavy, Esq. Knoble & Yoshida LLC, Eight Penn Center, Suite 1350  
1628 John F. Kennedy Boulevard, Philadelphia, PA 19103

Direct Telephone Calls to: (name and telephone number)

Kevin J. Dunleavy, Esq., 215-599-0600 or 703-851-3456

Full name of sole or first inventor <b>SUYKER, Wilhelmus Joseph Leonardus</b>	Date <b>Nov. 6, 2000</b>
Sole or first inventor's signature 	
Residence <b>Zalmkoik 13, NL-8017 PB ZWOLLE The Netherlands</b>	
Citizenship <b>The Netherlands</b>	
Post Office Address <b>Same as above</b>	

Full name of second inventor, if any <b>SUYKER, Paulus Thomas Wilhelmus</b>	Date <b>Nov. 7, 2000</b>
Second inventor's signature 	
Residence <b>Singel 298 F, NL-1016 AA AMSTERDAM The Netherlands</b>	
Citizenship <b>The Netherlands</b>	
Post Office Address <b>Same as above</b>	